

COLORES / COLOURS



PORCELÁNICO — BIA PORCELÁNICO

Model	Size	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
BETON BEIGE 60X60	60x60 24"x24"R	Mohs 3	Complies	<= 0,5%	Complies	> 35N/mm2	Class 2	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 3	-
BETON GREY 60X60	60x60 24"x24"R	Mohs 3	Complies	<= 0,5%	Complies	> 35N/mm2	Class 2	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 3	-
BETON SNOW 60X60	60x60 24"x24"R	Mohs 3	Complies	<= 0,5%	Complies	> 35N/mm2	Class 3	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 3	-
BETON BEIGE 60X120	60x120 24"x48"	Mohs 3	Complies	<= 0,5%	Complies	> 35N/mm2	Class 2	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 3	-
BETON SNOW 60X120	60x120 24"x48"R	Mohs 3	Complies	<= 0,5%	Complies	> 35N/mm2	Class 3	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 3	-
BETON GREY 60X120	60x120 24"x48"R	Mohs 3	Complies	<= 0,5%	Complies	> 35N/mm2	Class 2	6,6-10-6/°C	Complies	Complies	Complies	GLA	GHA	GA	Class 5	Class 3	-

1. Surface hardness degree (MOHS) *(EN 101)*

2. Dimensions and superficial aspect *(UNE EN ISO 10545-2)*

3. Water absorption (%) *(UNE EN ISO 10545-3)*

4. Breaking strength (N) *(UNE EN ISO 10545-4)*

5. Modulus of rupture (N/mm²) *(UNE EN ISO 10545-4)*

6. Abrasion resistance *(UNE EN ISO 10545-7)*

7. Lineal thermic expansion coefficient *(UNE EN ISO 10545-8)*

8. Thermal shock resistance *(UNE EN ISO 10545-9)*
9. Cracking resistance *(UNE EN ISO 10545-11)*

10. Frost resistance *(UNE EN ISO 10545-12)*

11. Chemical resistance — weak acids/bases *(UNE EN ISO 10545-13)*

12. Chemical resistance — strong acids/bases *(UNE EN ISO 10545-13)*

13. Chemical resistance — Domestic cleaning *(UNE EN ISO 10545-13)*

14. Stains resistance *(UNE EN ISO 10545-14)*

15. Slip resistance *(UNE ENV 12633/2003 — DIN 51130/2010)*

16. DCOF *(DCOF)*

PACKAGING

Size	Box			Pallet			Euro Pallet		
	PCS	M²	KG	BOX	M²	KG	BOX	M²	KG
60x60 (24"x24"R)	4	1	37	—	—	—	40	57	960
60x120 (24"x48")	3	2.16	37.93	0	0	0	29	62.64	1100